

			型号								
			Unit	FT-400K(S)		FT-600K(S)		FT-800K(S)		FT-800K(S) 高速机	
射出系统 Injection Unit	螺杆直径	Screw diameter	mm	φ25		φ25		φ25		φ20	
	射出压力	Maximum injection pressure	kg/cm ²	2509		2509		2509		3500	
	理论射出容积	Theoretical injection volume	cm ³	59		59		59		31.4	
	射出重量 (PS)	Maximum injection weight (PS)	g	54.5		54.5		54.5		29	
			oz	1.9		1.9		1.9		1.0	
射出率	Injection rate	cm ³ /sec	34		45		68		53		
锁模系统 Clamping Unit	锁模力	Clamping force	ton	40		70		100		100	
	上模板尺寸	Top platen size	mm	550×395		610×460		700×550		700×550	
	下模板尺寸	Bottom Table Size	mm	590×435		660×550		740×590		740×590	
	单滑板尺寸	Sliding Table Size	mm	390×400		450×490		500×580		500×580	
	单滑板行程	Sliding Table Stroke	mm	420		500		590		590	
	容模尺寸	Mold Size	mm	410×255		460×310		510×360		510×360	
	最小模厚	Minimum mold thickness	mm	150/250		200/300		200/300		150	
	开模行程	Opening stroke	mm	200		250		270		270	
	最大开模距离	Open daylight	mm	350/450		450/550		470/570		420/520	
	顶出力	Ejector force	ton	1.3	1.5	1.7	2	2.2	2.7	2.2	2.7
	顶出高度	Ejector Hight	mm	35	55	45	65	65	55	65	55
	系统最大压力	Hydraulic system pressure	kgf/cm ²	140		140		140		140	
其他 Others	油箱容积	Oil tank capacity	L	195		245		390		390	
	油泵电机	Motor power(pump)	kW	5.5		7.5		11		11	
	电热容量	Barrel heating power	kW	3.6		3.6		3.6		3.6	
	总用电量	Total wattage	kW	9.1		11.1		14.6		15	
	机器尺寸	Machine Size (L×W×H)	m	1.8×1.0×2.4	2.0×1.0×2.5	1.9×1.1×2.9	2.2×1.1×3.0	2.0×1.3×3.1	2.4×1.3×3.2	2.1×1.4×3.4	2.5×1.4×3.5
	机器重量	Machine Weight	t	1.4	1.6	2	2.3	2.5	3	2.5	3