

规格参数 SPECIFICATION

射出单元选项		Injection unit option	Unit	A射座	B射座
射出系统 Injection Unit	螺杆直径	Screw diameter	mm	φ25	φ20
	射出压力	Maximum injection pressure	kgf/cm ²	2508	1814
	理论射出容积	Theoretical injection volume	cm ³	59	49
	射出重量	Maximum injection weight(ps)	g	54.5	45
oz			1.9	1.6	

射出单元选项		Injection unit option	Unit	型号						
				FT-800K-2RC		FT-1200K-2RC		FT-1200K-3R3C		
			NO.	A+A		A+A		A+A+B		
锁模系统 Clamping Unit	锁模力	Theoretical injection volume	ton	40	40	60	60	60+60		
	上模板尺寸	Top platen size	mm	540X480	540X480	540X600	540X600	1060×730		
	圆盘直径	Rotary table diameter	mm	φ800		φ1000		φ800		
	最大模具尺寸	Maximum mold size	mm	250X180		400X300		300×260		
	最小模厚	Minimum mold thickness	mm	150+100		200/300		250		
	开模行程	Opening stroke	mm	200		250		300		
	最大开模距	Open daylight	mm	350/100		450/550		550		
	顶出力	Ejector force	ton	1.3		1.7		1.5		
	顶出高度	Ejector stroke	mm	35		45		50		
其他 Others	系统最大压力	Hydraulic system pressure	kgf/cm ²	140		140		140		
	油箱容积	Oil tank capacity	L	400		700		600		
	油泵电机	Motor power(Pump)	kw	5.5	5.5	11	11	15+11		
	电热容量	Barrel heating power	kw	3.6	3.6	3.6	3.6	3.6	3.6	2.7
	总用电量	Total wattage	kw	18.2		29.2		35.9		
	机器尺寸	Machine dimensions	m	2.0X1.5X3		2.5X1.9X3.3		2.6×1.6×3.6		
	机器重量	Machine weight	ton	4		5.5		5.5		